

Listing of Claims:

1. (Previously Presented) A camera system comprising:
a camera body; and
an accessory device to be releasably mounted on the camera
body;

5 wherein the camera body comprises a camera side
identification data table, a specifying section which specifies
an appropriate data address to the accessory device, and a
judging section;

10 wherein the accessory device comprises an accessory device
side identification data table congruous with at least one part
of the camera side identification data table, and a transmitting
section which transmits the identification data stored in the
accessory device side identification data table at the data
address specified by the specifying section to the camera body;
15 and

20 wherein the judging section is adapted to determine if a
dedicated accessory is mounted by comparing the identification
data transmitted back from the accessory device and the
identification data stored in the camera side identification data
table at the address corresponding to the data address.

2. (Previously Presented) The camera system according to claim 1, wherein each of the camera body and the accessory device comprises a plurality of identification data tables, and wherein the camera body specifies one of the plurality of identification data tables and an appropriate address of the specified table to the accessory device.

3. (Previously Presented) The camera system according to claim 1, wherein the accessory device comprises an interchangeable lens that is releasably mounted on the camera body.

4. (Previously Presented) The camera system according to claim 1, wherein the accessory device comprises a flash unit that is releasably mounted on the camera body.

5. (Previously Presented) The camera system according to claim 1, wherein the accessory device comprises a battery pack that is releasably mounted on the camera body.

6. (Previously Presented) An accessory device to be releasably mounted on a camera body having a functional feature of determining if an accessory device dedicated to the camera body is mounted thereon, the accessory device comprising:

5 an identification data table held congruous with at least
one part of a camera side identification data table provided in
the camera body; and

 a transmitting section which selects an identification data
in the identification data table and transmits the selected
10 identification data to the camera body in response to a
specification by the camera body.

7. (Previously Presented) The accessory device according
to claim 6, wherein the accessory device comprises an
interchangeable lens that is releasably mounted on the camera
body.

8. (Previously Presented) The accessory device according
to claim 6, wherein the accessory device comprises a strobe unit
that is releasably mounted on the camera body.

9. (Previously Presented) The accessory device according
to claim 6, wherein the accessory device comprises a battery pack
that is releasably mounted on the camera body.

10. (Previously Presented) A camera body having a
functional feature of determining if an accessory device designed

to be dedicated to ~~it~~ the camera body is mounted thereon, the camera body comprising:

- 5 an identification data table including an accessory side identification data table held by the accessory device;
- a specifying section which specifies an appropriate data address to the accessory device; and
- a judging section which determines if the dedicated
- 10 accessory device is mounted thereon by comparing (i) identification data corresponding to the specified data address of the accessory side identification data table and transmitted back from the accessory device according to a specification by the specifying section, and (ii) identification data stored in
- 15 the camera side identification data table at an address corresponding to the specified data address.

11. (Previously Presented) The camera body according to claim 10, wherein the accessory device comprises an interchangeable lens that is releasably mounted on the camera body.

12. (Previously Presented) The camera body according to claim 10, wherein the accessory device comprises a strobe unit that is releasably mounted on the camera body.

13. (Previously Presented) The camera body according to claim 10, wherein the accessory device comprises a battery pack that is releasably mounted on the camera body.

14. (Previously Presented) A camera system comprising:
a camera body; and
an accessory device to be releasably mounted on the camera body;

5 wherein the camera body comprises a camera side memory section storing identification data congruous with identification data stored in the accessory device, a detecting section which detects a predetermined operation by a user, a comparing section, and a judging section;

10 wherein the accessory device comprises an accessory device side memory section storing identification data congruous with the identification data stored in the camera body;

15 wherein the comparing section is arranged in the camera body to receive identification data from the accessory device when the predetermined operation is detected by the detecting section, and to compare the identification data with corresponding camera side identification data;

20 wherein the judging section is adapted to judge if the dedicated accessory device is mounted on the camera body according to a result of comparison by the comparing section; and

wherein a restricting section inhibits/restricts operation of the camera thereafter if the judging section judges that the dedicated accessory device is not mounted on the camera body.

15. (Previously Presented) The camera system according to claim 14, further comprising:

a specifying section arranged in the camera body to specify an appropriate data address to the accessory device when the
5 predetermined operation is detected by the detecting section; and

a transmitting section arranged in the accessory device to transmit the identification data stored in the accessory device side identification data table to the camera body according to the specified data address.

16. (Previously Presented) The camera system according to claim 15, wherein each of the camera side memory section and the accessory device side memory section comprises a plurality of data tables formed by a plurality of identification data, and
5 wherein the camera body specifies one of the plurality of data tables and an appropriate address of the specified table to the accessory device.

17. (Previously Presented) The camera system according to claim 14, wherein the accessory device comprises an

interchangeable lens that is releasably mounted on the camera body.

18. (Previously Presented) The camera system according to claim 14, wherein the accessory device comprises a strobe unit that is releasably mounted on the camera body.

19. (Previously Presented) The camera system according to claim 14, wherein the accessory device comprises a battery pack that is releasably mounted on the camera body.

Claims 20-48 (Canceled).

49. (Previously Presented) A camera system comprising a camera body and an accessory to be releasably mounted on the camera body, the system comprising:

5 a camera side arithmetic section arranged in the camera body to store an arithmetic expression to be used for performing a predetermined arithmetic operation;

an accessory side arithmetic section arranged in the accessory to store an arithmetic expression congruous with the arithmetic expression of the camera side arithmetic section;

10 an arithmetic operation data outputting section arranged in the camera body to output arithmetic operation data common to the

camera side arithmetic section and the accessory side arithmetic section; and

15 a judging section arranged in the camera body to compare an outcome of the arithmetic operation performed by the camera side arithmetic section and an outcome of the arithmetic operation performed by the accessory side arithmetic section and to judge that a right accessory is mounted on the camera body when the outcomes agree with each other.

50. (Previously Presented) The camera system according to claim 49, wherein the arithmetic operation data outputting section outputs a plurality of numerical values, and both the camera side arithmetic section and the accessory side arithmetic
5 section perform the arithmetic operations using a same numerical value selected from the plurality of numerical values.

51. (Previously Presented) The camera system according to claim 49, wherein the arithmetic operation data include data to be used for the arithmetic operations and dummy data.

52. (Previously Presented) The camera system according to claim 49, wherein the arithmetic operation data include a plurality of numerical value data including data for specifying

data to be used for the arithmetic operations, data to be used in
5 the arithmetic operations, and dummy data.

53. (Previously Presented) The camera system according to
claim 49, wherein the arithmetic operation data include a
plurality of numerical value data, and

wherein the camera side arithmetic section and the accessory
5 side arithmetic section have a plurality of arithmetic
expressions in common, and are adapted to select one of the
plurality of arithmetic expressions by using specific data
selected from the plurality of numerical value data output from
the arithmetic operation data outputting section.

54. (Previously Presented) The camera system according to
claim 53, wherein the plurality of numerical value data include
data for specifying an arithmetic expression, data for specifying
the data to be used for the arithmetic operations, data to be
5 used in the arithmetic operations, and dummy data.

55. (Previously Presented) The camera system according to
claim 49, wherein the arithmetic operation data outputting
section includes a random number generating section and outputs
the arithmetic operation data based on a random number generated
5 by the random number generating section.

56. (Previously Presented) A camera to which an accessory to be releasably mounted, the camera comprising:

a camera side arithmetic section that stores an arithmetic expression congruous with an arithmetic expression stored in an accessory side arithmetic section possessed by the accessory;

an arithmetic operation data outputting section that outputs arithmetic operation data to the accessory side arithmetic section and the camera side arithmetic section; and

a judging section that receives an outcome of an arithmetic operation of the camera side arithmetic section and an outcome of an arithmetic operation of the accessory side arithmetic section and judges if the accessory is a right accessory by comparing the outcomes.

57. (Previously Presented) The camera according to claim 56, wherein the camera becomes inoperative when the judging section judges that the accessory is not the right accessory.

58. (Previously Presented) A judgment control method to be used by an accessory that is to be releasably mounted on a camera body, the method comprising:

receiving at an accessory side a plurality of numerical value data from the camera body;

selecting data to be used for an arithmetic operation for judgment control of the accessory out of the plurality of numerical value data;

10 performing the arithmetic operation for judgment control of the accessory using the selected data; and

transmitting an outcome of the arithmetic operation for judgment control to the camera body.

59. (Previously Presented) A judgment control method to be used by an accessory that is to be releasably mounted on a camera body, the method comprising:

5 receiving at an accessory side a plurality of numerical value data from the camera body;

selecting data to be used for an arithmetic operation for judgment control of the accessory out of the plurality of numerical value data according to a specific one of the plurality of numerical value data;

10 performing the arithmetic operation for judgment control of the accessory using the selected data; and

transmitting an outcome of the arithmetic operation for judgment control to the camera body.

60. (Previously Presented) A judgment control method to be used by an accessory that is to be releasably mounted on a camera body, the method comprising:

receiving at an accessory side a plurality of data from the
5 camera body;

determining an arithmetic expression to be used for an arithmetic operation for judgment control of the accessory according to first data of the plurality of data;

selecting third data from the plurality of data according to
10 second data of the plurality of data;

performing the arithmetic operation for judgment control of the accessory using the selected arithmetic expression and the selected third data; and

transmitting an outcome of the arithmetic operation for
15 judgment control to the camera body.

61. (Previously Presented) A camera system comprising a camera body and an interchangeable lens to be releasably mounted on the camera body, the system comprising:

a camera side arithmetic section arranged in the camera body
5 to store an arithmetic expression to be used for performing a predetermined arithmetic operation;

a lens side arithmetic section arranged in the interchangeable lens to store an arithmetic expression congruous

with the arithmetic expression of the camera side arithmetic
10 section;

an arithmetic operation data outputting section arranged in
the camera body to output arithmetic operation data common to the
camera side arithmetic section and the lens side arithmetic
section; and

15 a judging section arranged in the camera body to compare an
outcome of the arithmetic operation performed by the camera side
arithmetic section and an outcome of the arithmetic operation
performed by the lens side arithmetic section and to judge that a
right interchangeable lens is mounted on the camera body when the
20 outcomes agree with each other.

62. (Previously Presented) The camera system according to
claim 61, wherein the arithmetic operation data outputting
section outputs a plurality of numerical values and both the
25 camera side arithmetic section and the lens side arithmetic
section perform the arithmetic operations using a same numerical
value selected from the plurality of numerical values.

63. (Previously Presented) The camera system according to
claim 61, wherein the arithmetic operation data include data to
be used for the arithmetic operations and dummy data.

64. (Previously Presented) The camera system according to claim 61, wherein the arithmetic operation data include a plurality of numerical value data including data for specifying the data to be used for the arithmetic operations, data to be
5 used in the arithmetic operations, and dummy data.

65. (Previously Presented) The camera system according to claim 61, wherein the arithmetic operation data include a plurality of numerical value data, and

wherein the camera side arithmetic section and the lens side
5 arithmetic section have a plurality of arithmetic expressions in common and are adapted to select one of the plurality of arithmetic expressions by using specific data selected from the plurality of numerical value data output from the arithmetic operation data outputting section.

66. (Previously Presented) The camera system according to claim 65, wherein the plurality of numerical value data include data for specifying an arithmetic expression, data for specifying the data to be used for the arithmetic operations, data to be
5 used in the arithmetic operations, and dummy data.

67. (Previously Presented) The camera system according to claim 61, wherein the arithmetic operation data outputting

section includes a random number generating section and outputs
the arithmetic operation data based on a random number generated
5 by the random number generating section.

68. (Previously Presented) A camera to which an
interchangeable lens is to be releasably mounted, the camera
comprising:

a camera side arithmetic section that stores an arithmetic
5 expression congruous with an arithmetic expression stored in an
lens side arithmetic section in the interchangeable lens;

an arithmetic operation data outputting section that outputs
arithmetic operation data to the lens side arithmetic section and
the camera side arithmetic section;

10 a judging section that receives an outcome of an arithmetic
operation of the camera side arithmetic section and an outcome of
an arithmetic operation of the lens side arithmetic section and
judges if the interchangeable lens is a right interchangeable
lens by comparing the outcomes.

69. (Previously Presented) The camera according to claim
68, wherein the camera becomes inoperative when the judging
section judges that the interchangeable lens is not the right
interchangeable lens.

70. (Previously Presented) A judgment control method to be used by an interchangeable lens that is to be releasably mounted on a camera body, the method comprising:

receiving at interchangeable lens side a plurality of
5 numerical value data from the camera body;

selecting data to be used for an arithmetic operation for judgment control of the interchangeable lens out of the plurality of numerical value data;

performing the arithmetic operation for judgment control of
10 the interchangeable lens using the selected data; and

transmitting an outcome of the arithmetic operation for judgment control to the camera body.

71. (Previously Presented) A judgment control method to be used by an interchangeable lens that is to be releasably mounted on a camera body, the method comprising:

receiving at an interchangeable lens side a plurality of
5 numerical value data from the camera body;

selecting data to be used for an arithmetic operation for judgment control of the interchangeable lens out of the plurality of numerical value data according to a specific one of the plurality of numerical value data;

performing the arithmetic operation for judgment control of
10 the interchangeable lens using the selected data; and

transmitting an outcome of the arithmetic operation for judgment control to the camera body.

72. (Previously Presented) A judgment control method to be used by an interchangeable lens that is to be releasably mounted on a camera body, the method comprising:

receiving at an interchangeable lens side a plurality of
5 data from the camera body;

determining an arithmetic expression to be used for an arithmetic operation for judgment control of the interchangeable lens according to a first data of the plurality of data;

selecting a third data from the plurality of data according
10 to a second data of the plurality of data;

performing the arithmetic operation for judgment control of the interchangeable lens using the selected arithmetic expression and the selected third data; and

transmitting an outcome of the arithmetic operation for
15 judgment control to the camera body.

73. (New) A camera system comprising a camera body and an accessory device to be releasably mounted on the camera body, the camera system further comprising:

a camera side identification data table in the camera body;

5 an accessory device side identification data table in the
accessory device, which is at least partially congruous with
the camera side identification data table;

 a specifying section arranged in the camera body to specify
a data address, which is selected in accordance with a
10 predetermined method, to the accessory device;

 a transmitting section arranged in the accessory device to
transmit identification data stored in the accessory device side
identification data table to the camera body in accordance with
the data address specified by the specifying section;

15 a detection switch to detect whether the accessory device
is mounted on the camera body; and

 a judging section arranged in the camera body to judge
whether a dedicated accessory device is mounted by, at least
when the detection switch detects that the accessory device is
20 mounted on the camera body, comparing the identification data
transmitted by the accessory device to identification data
stored in the camera side identification data table and
corresponding to the data address;

 wherein operation of the camera system is restricted when
25 the judging section judges that the dedicated accessory is not
mounted, relative to operation of the camera system when the
judging section judges that the dedicated accessory is mounted.

74. (New) The camera system according to claim 73,
wherein each of the camera body and the accessory device has a
plurality of identification data tables, and wherein the camera
body specifies one of the plurality of identification data
5 tables and an appropriate address of the specified table to the
accessory device.

75. (New) The camera system according to claim 73,
wherein the accessory device comprises at least one of an
interchangeable lens, a flash unit and a battery pack, which is
releasably mounted on the camera body.

76. (New) The camera system according to claim 73,
wherein the camera body is prohibited from operating when the
judging section judges that the dedicated accessory is not
mounted.

77. (New) The camera system according to claim 73,
wherein the accessory device is prohibited from operating when
the judging section judges that the dedicated accessory is not
mounted.